VOLVO PENTA

AB Volvo Penta SE-405 08 Göteborg Sweden Service Bulletin
Group Number Version
44-1 85 2

Changed oil quality recomendation for S-drives

130S-A, 130S-B, 130SR-A, 130SR-B, 150S-A, 150S-B, 150SR-A, 150SR-B

Binder: Date: 10-2010 Page: 1(1)

SAE 15W40 ONLY

P0014226

Volvo Penta has changed the recommendation for oil quality in S-drives.

S-drives manufactured September 2010 onwards will have a sticker with the information "SAE 15W-40 ONLY" attached in connection to the oil filler. Older drives have a sticker with the text "ATF OIL ONLY".

Volvo Penta recommends that all S-drives change from ATF oil to engine oil SAE 15W-40 at next oil change.

It is possible to replace oil without laying up the boat, pelase refer to the Operator's Manual. However, with this method some ATF oil will remain in the stern drive.

For problems concerning sliding / delayed engagement Volvo Penta recommend change of disk package and replacing the oil with engine oil SAE 15W-40.

IMPORTANT!

Gear when sailing

When sailing, set the control lever to reverse if a folding propeller is fitted.

If a fixed propeller is fitted the control lever should be set in neutral or reverse. When using a fixed propeller and sailing with the control lever set to reverse the speed is slowed down though less noise is being made.